



RUNCO® VIDEOXTREME™ VX-22i 3-CHIP PROJECTOR

Runco has taken 1080p performance to a new level with the VX-22i and harnessed the brightness and contrast capabilities inherent in 3-chip light engine design for impressive images. Supplied with Runco's advanced Vivix™ video processing, superb scaling and aspect ratio control, the Runco VX-22i takes full advantage of Runco's engineering advances.



Projector Type:	Digital Light Processing™ (DLP™), 3-Chip, 16:9 SuperOnyx™ DMD™
Native Resolution:	1920x1080 (1080p)
DTV Compatibility:	480p, 720p, 1080i, 1080p
Picture Size:	(16:9 screens):Recommended Width: 80 - 180 inches
Maximum Width:	250 inches
Light Output:	CSMS Specifications: Home Theater
Calibration:	1505 ANSI Lumens; 97 Foot-Lamberts (fL); 2,300 ANSI Lumens (uncalibrated)†
Contrast Ratio:	CSMS Contrast Ratio: >400:1 (ANSI);4000:1 full-on, full-off (native)
Throw Distance Factor x Screen Width:	Triton Lens Options: A-1: Fixed 0.70 (for rear-screen applications) A-2: Foxed 1.16 (for rear-screen applications) B: Zoom 1.40 - 1.81 C: Zoom 1.85 - 2.53 (w/CW McKinley only, 1.40 - 1.90) D: Zoom 2.65 - 4.20 (w/CW McKinley only, 2.02- 3.15) E: Zoom 4.30 - 7.00 (w/CW Rainier only, 3.14 - 5.50)
Horizontal & Vertical Offset Without CineWide option: (CineWide option offsets vary per lens. Please contact Runco Tech Support for info)	Varies per lens option Triton A-1: Vertical: 10% up/down; 5% horizontal Triton A-2: Vertical: 31% up, 71% down; 17% horizontal Triton B: Vertical: 30% up, 61% down; 12% horizontal Triton C: Vertical: 32% up, 62% down; 12% horizontal Triton D: Vertical: 28% up, 65% down; 12% horizontal Triton E: Vertical: 30% up, 63% down; 12% horizontal

For more information visit www.Runco.com or call 800-237-8626 or +1-503-748-1100.

Specifications are subject to change without notice. ©Copyright 2010 Runco International Inc. All rights reserved.



RUNCO® VIDEOXTREME™ VX-22i 3-CHIP PROJECTOR



Lamp:	300W
Lamp Life:	2000 hours
Inputs:	(1) Composite; (1) S-video; (1) VGA; (2) HD - 1 each RB, BNC - R (Pr), G (Y), B (Pb), H, V; (2) HDMI w/HDCP
12V Output:	(3) +12 VDC, each rated at 750 mA and thermal fuse protected
Power Requirements:	100 - 240V VAC (auto-sensing), 50/60 Hz, 570W
Operating Environments:	40 to 95°F (5 to 35°C); 0-90% humidity (non-condensing)
Dimensions:	Width: 20.81in. (528 mm) Depth: 29.77 in. (756 mm) Height: 10.04in. (255mm) Weight: 99.21 lbs. (45.00 kg) (without lens)
Regulatory Approvals:	Both projector and DHD comply with FCC, CE C-Tick
Limited Warranty:	Projector & DHD: Two years parts and labor from the date of shipment from Runco. RuncoCare™ and Runco RedCarpet™ plans available.
Lamp Warranty:	1000 hours or (6) Six months, whichever comes first.

* Measured Screen Width on a 1.3 gain, 72" wide 16:9 screen; * Triton Lens options: distance/screen width +/-2.5%

For more information visit www.Runco.com or call 800-237-8626 or +1-503-748-1100.